

(19)



Europäisches Patentamt
European Patent Office
Office européen des brevets



(11)

EP 1 197 535 A2

(12)

EUROPEAN PATENT APPLICATION

(43) Date of publication:

17.04.2002 Bulletin 2002/16

(51) Int Cl.7: **C09D 11/02**

// C09B29/40, C09B29/036

(21) Application number: **01203710.7**

(22) Date of filing: **01.10.2001**

(84) Designated Contracting States:

**AT BE CH CY DE DK ES FI FR GB GR IE IT LI LU
MC NL PT SE TR**

Designated Extension States:

AL LT LV MK RO SI

(30) Priority: **12.10.2000 US 689184**

(71) Applicant: **EASTMAN KODAK COMPANY**
Rochester, New York 14650 (US)

(72) Inventors:

- **Evans, Steven**
Rochester, New York 14650-2201 (US)

- **Weber, Helmut**

Rochester, New York 14650-2201 (US)

- **Pyszczyk, Ellen Marie**

Rochester, New York 14650-2201 (US)

- **Carroll-Lee, Ann L.**

Rochester, New York 14650-2201 (US)

(74) Representative:

Nunney, Ronald Frederick Adolphe et al
Kodak Limited,
Patents, W92-3A,
Headstone Drive
Harrow, Middlesex HA1 4TY (GB)

(54) **Ink-jet ink composition containing a pyrazoleazoindole dye**

(57) **An ink jet ink composition comprising water, a humectant and a water-soluble pyrazoleazoindole dye.**

EP 1 197 535 A2

Description

[0001] This invention relates to the use of a pyrazoleazoindole dye as a colorant in an ink jet composition.

[0002] Ink jet printing is a non-impact method for producing images by the deposition of ink droplets in a pixel-by-pixel manner to an image-recording element in response to digital signals. There are various methods which may be utilized to control the deposition of ink droplets on the image-recording element to yield the desired image. In one process, known as continuous ink jet, a continuous stream of droplets is charged and deflected in an imagewise manner onto the surface of the image-recording element, while unimaged droplets are caught and returned to an ink sump. In another process, known as drop-on-demand ink jet, individual ink droplets are projected as needed onto the image-recording element to form the desired image. Common methods of controlling the projection of ink droplets in drop-on-demand printing include piezoelectric transducers and thermal bubble formation. Ink jet printers have found broad applications across markets ranging from industrial labeling to short run printing to desktop document and pictorial imaging.

[0003] The inks used in the various ink jet printers can be classified as either dye-based or pigment-based. A dye is a colorant, which is dissolved in the carrier medium. A pigment is a colorant that is insoluble in the carrier medium, but is dispersed or suspended in the form of small particles, often stabilized against flocculation and settling by the use of dispersing agents. The carrier medium can be a liquid or a solid at room temperature in both cases. Commonly used carrier media include water, mixtures of water and organic co-solvents and high boiling organic solvents, such as hydrocarbons, esters, ketones, etc.

[0004] The choice of a colorant in ink jet systems is critical to image quality. For colors such as cyan, magenta, yellow, green, orange, etc., the peak wavelength (λ -max), the width of the absorption curve and the absence of secondary absorptions are important. The colorant should also have a high degree of light fastness after printing onto the ink-receiving element. For aqueous dye-based inks, the dye needs to be sufficiently soluble in water to prepare a solution that is capable of producing adequate density on the receiving element and stable for extended periods of storage without precipitation. High quality ink jet printing with dye-based inks requires dyes which will provide both bright hue and good light stability. It is difficult to find dyes, particularly yellow dyes, which meet all of these requirements.

[0005] Aqueous dye-based inks for high-quality, photo-realistic, ink jet printing require water-soluble dyes with excellent color and high light- and waterfastness. Typically the dyes are chosen from acid, direct and reactive dyestuffs developed for the dyeing of natural fibers such as paper, wool and cotton. Water solubility of these dyes is due to the incorporation of negatively charged substituent groups such as sulfo or carboxy.


[0006] U.S.S.N. 09/306,121, filed May 6, 1999, discloses water-soluble azoindole dyes for use in ink jet printing including dyes derived from diazotizable heteroaromatic amines. However, there is a problem with some of these dyes in that they do not have sufficient light stability.

[0007] U.S. Patent 4,685,934 describes water-soluble pyrazoleazoindole yellow and orange dyes useful for conventional dyeing of synthetic fibers and textiles. However, there is no disclosure in this patent for use of these dyes in ink jet printing.

[0008] It is an object of this invention to provide bright, readily water-soluble and light stable azoindole dyes derived from diazotizable heteroaromatic amines useful for aqueous ink jet printing.

[0009] This and other objects are achieved in accordance with this invention which relates to an ink jet ink composition comprising water, a humectant and a water-soluble pyrazoleazoindole dye.

[0010] In a preferred embodiment of the invention, the pyrazoleazoindole dyes employed in the invention may be represented by the following structure:



I

wherein:

R_1 and R_3 each independently represents hydrogen, a substituted or unsubstituted alkyl group of 1-6 carbon atoms, a substituted or unsubstituted allyl group, a substituted or unsubstituted aryl group of 6-10 carbon atoms, a substituted or unsubstituted heteroaryl group of 5-10 atoms or a polyoxyalkylene group of 2-20 alkylene oxide residues; R_2 , X and Y each independently represents the groups listed above for R_1 , halogen, cyano, carboxy, acyl, nitro, sulfo, a substituted or unsubstituted alkoxy group of 1-6 carbon atoms, a substituted or unsubstituted aryloxy group of 6-10 carbon atoms, a substituted or unsubstituted alkoxy- or aryloxy-carbonyl group of 1-10 carbon atoms, a polyoxyalkylene group of 2-20 alkylene oxide residues, a ureido group, carbamoyl, a substituted or unsubstituted alkyl-, arylalkyl-, aryl-, diaryl- or dialkyl-carbamoyl group of 1-20 carbon atoms, sulfamoyl, a substituted or unsubstituted alkyl-, arylalkyl-, aryl-, diaryl- or dialkyl-sulfamoyl group of 1-20 carbon atoms, acylamino, sulfonylamino, amino, or a substituted or unsubstituted alkyl-, aralkyl-, aryl-, diaryl- or dialkyl-amino group of 1-20 carbon atoms; n represents an integer from 1-4; and Z represents cyano, carboxy, sulfo, alkoxy-carbonyl, carbamoyl or a substituted or unsubstituted alkyl-, arylalkyl-, aryl-, diaryl- or dialkyl-carbamoyl group of 1-20 carbon atoms; with the proviso that the dye must contain at least one group capable of imparting water solubility at a pH of 4-9.

[0011] In a preferred embodiment of the invention, R_1 in the above formula represents hydrogen, methyl or 2-carboxyethyl. In another preferred embodiment, R_2 represents methyl or phenyl. In still another preferred embodiment, X represents hydrogen, sulfo, a substituted 1,3,5-triazinylamino group or an N-alkylphthalamido group. In yet another preferred embodiment, R_3 represents 4-sulfophenyl, 2,5-bis-sulfophenyl, methyl, phenyl, 4-carboxyphenyl or 3-sulfopropyl. In yet another preferred embodiment, Y represents hydrogen. In still yet another preferred embodiment Z represents cyano, carboxy or carbamoyl.

[0012] In the above definition, examples of a substituted or unsubstituted alkyl group include methyl, ethyl, isopropyl, hydroxyethyl, 3-sulfopropyl and m-carboxybenzyl. Examples of a substituted or unsubstituted aryl group include phenyl, naphthyl, 3,5-bis-carboxyphenyl and 4-sulfophenyl. Examples of a substituted or unsubstituted heteroaryl group include pyridyl, imidazolyl and quinolyl. Examples of halogen include chloro, fluoro, bromo and iodo. Examples of an acyl group include acetyl and 4-sulfobenzoyl. Examples of a substituted or unsubstituted alkoxy group include methoxy, 3-carboxypropoxy and 2-hydroxyethoxy. Examples of a substituted or unsubstituted aryloxy group include phenoxy, 3-carboxyphenoxy and 4-sulfophenoxy. Examples of a substituted or unsubstituted alkoxy- or aryloxy-carbonyl group of 1-10 carbon atoms include methoxycarbonyl, ethoxycarbonyl, 2-methoxyethoxycarbonyl and 3-sulfophenoxycarbonyl. Examples of a substituted or unsubstituted alkyl-, aralkyl-, aryl-, diaryl- or dialkyl carbamoyl group include N-methylcarbamoyl, N-methyl-N-4-sulfophenyl-carbamoyl, N,N-bis (4-carboxyphenyl)carbamoyl. Examples of a substituted or unsubstituted alkyl-, aralkyl-, aryl-, diaryl- or dialkyl sulfamoyl group include N-methylsulfamoyl, N-methyl-N-phenyl-sulfamoyl, N-(p-sulfophenyl)sulfamoyl and N,N-bis (4-carboxyphenyl)sulfamoyl. Examples of an acylamino group include acetamido, methoxyethylacetamido and 3-carboxybenzamido. Examples of a ureido group include N-methylureido, ureido and N,N'-dimethylureido. Examples of a sulfonylamino group include methanesulfonamido, p-toluenesulfonamido and 2-sulfatoethanesulfonamido. Examples of a substituted or unsubstituted alkyl-, aralkyl-, aryl-, diaryl- or dialkylamino group include methylamino, N,N-dimethylamino, methoxyethylamino and 3-sulfoanilino.

EP 1 197 535 A2

[0013] Examples of groups capable of imparting water solubility at a pH of 4-9 include sulfonic, sulfinic, phosphonic, phosphoric and carboxylic acid moieties and salts thereof; primary, secondary and tertiary amino groups; and quaternary ammonium or phosphonium groups.

[0014] The dyes employed in the invention are not new and may be prepared by the methods disclosed in the above references or in Dyes and Pigments, Vol 2, pp. 305-318 (1981).

[0015] Representative examples of the pyrazoleazoindole dyes employed in this invention are listed below.

10

15

20

25

30


35

40

45


50

55




Dye	R_1	R_2	R_3	X	Z
1	$C_2H_4CO_2H$	C_6H_5	CH_3	H	CN
2	H	C_6H_5	H	$SO_3^- Na^+$	CN
3	$C_2H_4CO_2H$	C_6H_5	H	H	CN
4	$C_2H_4CO_2H$	CH_3	CH_3	H	CN
5	CH_2CO_2H	CH_3	CH_3	H	CN
6	CH_3	CH_3		H	CN
7	$C_2H_4CO_2H$	CH_3		H	CN
8	$C_2H_4CO_2H$	CH_3		H	CN
9	H	CH_3		H	CN
10	CH_3	CH_3		$SO_3^- Na^+$	$CONH_2$
11	$C_2H_4CO_2H$	CH_3		H	CO_2H


55 [0016] Other dyes within the scope of this invention include:




Dye 12




Dye 13



Dye 14



Dye 15



Dye 16

[0017] In general, the above dyes comprise from 0.2 to 8 %, preferably from 1 to 5 % by weight of the ink jet ink composition.

[0018] A humectant is employed in the ink jet composition of the invention to help prevent the ink from drying out or crusting in the orifices of the printhead. Examples of humectants which can be used include polyhydric alcohols, such as ethylene glycol, diethylene glycol, triethylene glycol, propylene glycol, tetraethylene glycol, polyethylene glycol, glycerol, 2-methyl-2,4-pentanediol, 1,2,6-hexanetriol and thioglycol; lower alkyl mono- or di-ethers derived from alkylene glycols, such as ethylene glycol mono-methyl or mono-ethyl ether, diethylene glycol mono-methyl or mono-ethyl ether, propylene glycol mono-methyl or mono-ethyl ether, triethylene glycol mono-methyl or mono-ethyl ether, diethylene glycol di-methyl or di-ethyl ether, and diethylene glycol monobutylether; nitrogen-containing cyclic compounds, such as pyrrolidone, N-methyl-2-pyrrolidone, and 1,3-dimethyl-2-imidazolidinone; and sulfur-containing compounds such as dimethyl sulfoxide and tetramethylene sulfone. A preferred humectant for the composition of the invention is diethylene glycol, glycerol, or diethylene glycol monobutylether.

[0019] Water-miscible organic solvents may also be added to the aqueous ink of the invention to help the ink penetrate the receiving substrate, especially when the substrate is a highly sized paper. Examples of such solvents include alcohols, such as methyl alcohol, ethyl alcohol, n-propyl alcohol, isopropyl alcohol, n-butyl alcohol, sec-butyl alcohol, t-butyl alcohol, iso-butyl alcohol, furfuryl alcohol, and tetrahydrofurfuryl alcohol; ketones or ketoalcohols such as acetone, methyl ethyl ketone and diacetone alcohol; ethers, such as tetrahydrofuran and dioxane; and esters, such as, ethyl lactate, ethylene carbonate and propylene carbonate.

[0020] Surfactants may be added to adjust the surface tension of the ink to an appropriate level. The surfactants may be anionic, cationic, amphoteric or nonionic.

[0021] A biocide may be added to the composition of the invention to suppress the growth of micro-organisms such as molds, fungi, etc. in aqueous inks. A preferred biocide for the ink composition of the present invention is Proxel® GXL (Zeneca Specialties Co.) at a final concentration of 0.0001-0.5 wt. %.

[0022] The pH of the aqueous ink compositions of the invention may be adjusted by the addition of organic or inorganic acids or bases. Useful inks may have a preferred pH of from 2 to 10, depending upon the type of dye being used. Typical inorganic acids include hydrochloric, phosphoric and sulfuric acids. Typical organic acids include methanesulfonic, acetic and lactic acids. Typical inorganic bases include alkali metal hydroxides and carbonates. Typical organic bases include ammonia, triethanolamine and tetramethylethylenediamine.

[0023] A typical ink composition of the invention may comprise, for example, the following constituents by weight: colorant (0.2-8%), water (20-95%), a humectant (5-70%), water miscible co-solvents (2-20%), surfactant (0.1-10%), biocide (0.05-5%) and pH control agents (0.1-10%).


[0024] Additional additives which may optionally be present in the ink jet ink composition of the invention include thickeners, conductivity enhancing agents, anti-kogation agents, drying agents, and defoamers.

[0025] The ink jet inks provided by this invention may be employed in ink jet printing wherein liquid ink drops are applied in a controlled fashion to an ink receptive layer substrate, by ejecting ink droplets from a plurality of nozzles or orifices of the print head of an ink jet printer.

[0026] Ink-receptive substrates useful in ink jet printing are well known to those skilled in the art. Representative examples of such substrates are disclosed in U.S. Patents 5,605,750; 5,723,211; and 5,789,070 and EP 813 978 A1.

[0027] The following examples illustrate the utility of the present invention.

[0028] The following control dyes were evaluated as comparative examples:



Dye	R ₁	R ₂	R ₃	X	Y	Z
C-1	H	C ₆ H ₅	C ₆ H ₅	SO ₃ ⁻ Na ⁺	CH ₃	H
C-2	H	CH ₃		H	C ₆ H ₅	H
C-3	C ₂ H ₄ CO ₂ H	C ₆ H ₅		H	C ₆ H ₅	H

Preparation of inks.

[0029] Inks containing the dyes employed in the invention and control dyes were prepared by dissolving an appropriate amount of the dye in deionized water containing humectants of diethylene glycol and glycerol, each at 6 wt. %, a biocide, Proxel GXL ® at 0.003 wt. % and a surfactant, Surfynol 465 ® (Air Products Co.) at 0.5 wt. %. The pH of each ink was adjusted to approximately 8 by adding triethanolamine. The dye concentrations were based on solution absorption spectra and chosen such that the final ink, when diluted 1:1000, would yield a transmission optical density of approximately 1.0. Details are given in the Table below.

Table 1

Ink	Dye	Wt. % Dye
1	1	1.83
2	2	2.9
3	3	2.12
4	4	1.39
5	5	1.32
6	6	2.53
7	7	1.95
8	8	1.68
9	9	2.56
10	10	3.43

EP 1 197 535 A2

Table 1 (continued)

Ink	Dye	Wt. % Dye
11	11	2.16
12	12	3.45
13	13	3.66
14	14	4.19
15	15	3.67
16	16	3.37
C-1	C-1	2.9
C-2	C-2	2.14
C-3	C-3	2.58

Printing of test images.

[0030] The above inks were then filtered through a 0.45 μ polytetrafluoroethylene filter and placed in a clean Hewlett-Packard ink cartridge No. HP 51629A and fitted into the black ink station of a Hewlett-Packard DeskJet 600 @ printer. A test image consisting of a series of 21 variable density patches, approximately 15 by 13 mm in size, ranging from 5% dot coverage to 100 % dot coverage was printed onto commercially-available Kodak Premium Picture Paper for Inkjet, Catalog No. 824-5276, and allowed to dry for 24 hours at ambient temperature and humidity.

Evaluation of test images

[0031] The printed images were bright yellow to yellow-orange in color. The Status A blue reflection densities of the maximum density patch (Blue D-max) of the above stepped images were measured using an X-Rite® 820 densitometer and are listed in the Table below. Values greater than 1.3 are acceptable.

[0032] The stepped images were then subjected to light fade under 50 Klux high-intensity daylight irradiation and 50% relative humidity conditions for 2 weeks. The Status A blue densities of the stepped images were remeasured and the % Status A blue density loss for the 75% dot coverage patches were calculated. Smaller % loss numbers represent more stable dyes and are preferred.

Table 2

Ink	Blue D-max	% Loss Light Fade
1	1.79	0
2	1.75	24
3	1.5	35
4	1.81	0
5	1.88	0
6	2.01	10
7	1.87	7
8	1.75	10
9	1.53	0
10	1.77	28
11	1.41	42
12	1.38	11
13	1.86	15
14	1.59	14


Table 2 (continued)

Ink	Blue D-max	% Loss Light Fade
15	2.0	22
16	1.73	25
C-1	1.83	73
C-2	1.42	84
C-3	1.6	82

[0033] The above data shows that inks containing the dyes employed in the invention yield more light stable images than closely related analogs. The printed images are also bright and of high density.

Claims

1. An ink jet ink composition comprising water, a humectant and a water-soluble pyrazoleazoindole dye.
2. The composition of Claim 1 wherein said water-soluble pyrazoleazoindole dye may be represented by the following structure:



I

wherein:

R_1 and R_3 each independently represents hydrogen, a substituted or unsubstituted alkyl group of 1-6 carbon atoms, a substituted or unsubstituted allyl group, a substituted or unsubstituted aryl group of 6-10 carbon atoms, a substituted or unsubstituted heteroaryl group of 5-10 atoms or a polyoxyalkylene group of 2-20 alkylene oxide residues;

R_2 , X and Y each independently represents the groups listed above for R_1 , halogen, cyano, carboxy, acyl, nitro, sulfo, a substituted or unsubstituted alkoxy group of 1-6 carbon atoms, a substituted or unsubstituted aryloxy group of 6-10 carbon atoms, a substituted or unsubstituted alkoxy- or aryloxy-carbonyl group of 1-10 carbon atoms, a polyoxyalkylene group of 2-20 alkylene oxide residues, a ureido group, carbamoyl, a substituted or unsubstituted alkyl-, arylalkyl-, aryl-, diaryl- or dialkyl-carbamoyl group of 1-20 carbon atoms, sulfamoyl, a substituted or unsubstituted alkyl-, arylalkyl-, aryl-, diaryl- or dialkyl-sulfamoyl group of 1-20 carbon atoms, acylamino, sulfonylamino, amino, or a substituted or unsubstituted alkyl-, aralkyl-, aryl-, diaryl- or dialkyl-amino group of 1-20 carbon atoms;

n represents an integer from 1-4; and

Z represents cyano, carboxy, sulfo, alkoxycarbonyl, carbamoyl or a substituted or unsubstituted alkyl-, arylalkyl-, aryl-, diaryl- or dialkyl-carbamoyl group of 1-20 carbon atoms;

with the proviso that the dye must contain at least one group capable of imparting water solubility at a pH of 4-9.

3. The composition of Claim 2 wherein R_1 represents hydrogen, methyl or 2-carboxyethyl.
- 5 4. The composition of Claim 2 wherein R_2 represents methyl or phenyl.
5. The composition of Claim 2 wherein X represents hydrogen, sulfo, a substituted 1,3,5-triazinylamino group or an N-alkylphthalamido group.
- 10 6. The composition of Claim 2 wherein R_3 represents 4-sulfophenyl, 2,5-bis-sulfophenyl, methyl, phenyl, 4-carboxyphenyl or 3-sulfopropyl.
7. The composition of Claim 2 wherein Y represents hydrogen.
- 15 8. The composition of Claim 2 wherein Z represents cyano, carboxy or carbamoyl.
9. The composition of Claim 1 wherein said humectant is diethylene glycol, glycerol or diethylene glycol monobutylether.
- 20 10. The composition of Claim 1 wherein said dye comprises 0.2 to 8 % by weight of said ink jet ink composition.

25

30

35

40

45

50

55

THIS PAGE BLANK (USPTO)

(19)



Europäisches Patentamt
European Patent Office
Office européen des brevets



(11)

EP 1 197 535 A3

(12)

EUROPEAN PATENT APPLICATION

(88) Date of publication A3:
12.11.2003 Bulletin 2003/46

(51) Int Cl.7: **C09D 11/02, C09B 29/00**
// C09B29/40, C09B29/036

(43) Date of publication A2:
17.04.2002 Bulletin 2002/16

(21) Application number: **01203710.7**

(22) Date of filing: **01.10.2001**

(84) Designated Contracting States:
AT BE CH CY DE DK ES FI FR GB GR IE IT LI LU
MC NL PT SE TR
Designated Extension States:
AL LT LV MK RO SI

(30) Priority: **12.10.2000 US 689184**

(71) Applicant: **EASTMAN KODAK COMPANY**
Rochester, New York 14650 (US)

(72) Inventors:
• **Evans, Steven**
Rochester, New York 14650-2201 (US)

• **Weber, Helmut**
Rochester, New York 14650-2201 (US)
• **Pyszczyk, Ellen Marie**
Rochester, New York 14650-2201 (US)
• **Carroll-Lee, Ann L.**
Rochester, New York 14650-2201 (US)

(74) Representative: **Haile, Helen Cynthia et al**
Kodak Limited
Patent, W92-3A,
Headstone Drive
Harrow, Middlesex HA1 4TY (GB)

(54) **Ink-jet ink composition containing a pyrazoleazoindole dye**

(57) **An ink jet ink composition comprising water, a humectant and a water-soluble pyrazoleazoindole dye.**

EP 1 197 535 A3



European Patent
Office

EUROPEAN SEARCH REPORT

Application Number
EP 01 20 3710

DOCUMENTS CONSIDERED TO BE RELEVANT			
Category	Citation of document with indication, where appropriate, of relevant passages	Relevant to claim	CLASSIFICATION OF THE APPLICATION (Int.Cl.7)
P,X	EP 1 052 274 A (EASTMAN KODAK CO) 15 November 2000 (2000-11-15) Table 1, Ink 1 ---	1,9,10	C09D11/02 C09B29/00 //C09B29/40, C09B29/036
P,X	EP 1 072 431 A (EASTMAN KODAK CO) 31 January 2001 (2001-01-31) Table 2, Ink Composition I-1 ---	1,9,10	
A	WO 98 14523 A (ZENECA LTD) 9 April 1998 (1998-04-09) * claims 1,17 * -----	1,9,10	
			TECHNICAL FIELDS SEARCHED (Int.Cl.7)
			C09D C09B
The present search report has been drawn up for all claims			
Place of search THE HAGUE		Date of completion of the search 16 September 2003	Examiner Saunders, T
<p>CATEGORY OF CITED DOCUMENTS</p> <p>X : particularly relevant if taken alone Y : particularly relevant if combined with another document of the same category A : technological background O : non-written disclosure P : intermediate document</p> <p>T : theory or principle underlying the invention E : earlier patent document, but published on, or after the filing date D : document cited in the application L : document cited for other reasons & : member of the same patent family, corresponding document</p>			

EPO FORM 1503 03/92 (P04C01)

**ANNEX TO THE EUROPEAN SEARCH REPORT
ON EUROPEAN PATENT APPLICATION NO.**

EP 01 20 3710

This annex lists the patent family members relating to the patent documents cited in the above-mentioned European search report. The members are as contained in the European Patent Office EDP file on
The European Patent Office is in no way liable for these particulars which are merely given for the purpose of information.

16-09-2003

Patent document cited in search report		Publication date		Patent family member(s)	Publication date
EP 1052274	A	15-11-2000	US	6136080 A	24-10-2000
			EP	1052274 A2	15-11-2000
			JP	2000319558 A	21-11-2000

EP 1072431	A	31-01-2001	US	6280028 B1	28-08-2001
			EP	1072431 A2	31-01-2001
			JP	2001080209 A	27-03-2001

WO 9814523	A	09-04-1998	AU	4310997 A	24-04-1998
			AU	4311797 A	24-04-1998
			AU	4311897 A	24-04-1998
			CN	1232481 A	20-10-1999
			CN	1232482 A	20-10-1999
			CN	1232483 A	20-10-1999
			DE	69702617 D1	24-08-2000
			DE	69702617 T2	08-03-2001
			DE	69709769 D1	21-02-2002
			DE	69709769 T2	29-05-2002
			DE	69718922 D1	13-03-2003
			EP	0929614 A1	21-07-1999
			EP	0929615 A1	21-07-1999
			EP	0929616 A1	21-07-1999
			WO	9814523 A1	09-04-1998
			WO	9814524 A1	09-04-1998
			WO	9814525 A1	09-04-1998
			JP	2001501246 T	30-01-2001
			JP	2001501999 T	13-02-2001
			JP	2001501661 T	06-02-2001
			KR	2000048787 A	25-07-2000
			KR	2000048788 A	25-07-2000
			KR	2000048789 A	25-07-2000
			US	6344497 B1	05-02-2002
			US	6200371 B1	13-03-2001
			US	6235096 B1	22-05-2001

EPO FORM P/459

For more details about this annex : see Official Journal of the European Patent Office, No. 12/82

THIS PAGE BLANK (USPTO)